

IP 2212 is a special PVC mesh featuring a film liner. It is intended for indoor and outdoor applications. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

IP 2212

IP 2212 is a fire retardant, flexible, digital mesh offering first class printability. This mesh can be used for indoor and outdoor applications such as see-thru advertising at trade shows and events, show rooms, construction sites and promotional campaigns. Although it is suited for trade show applications it is not resistant to creasing. The fabric features a very regular structure and offers excellent flat hanging properties.

Laminate: ImagePerfect™ water-based liquid laminate with UV protection.

Specifications	
DESCRIPTION	PVC mesh
COLOUR	White
FACE FILM THICKNESS	400μ
WEIGHT	260g / m ²
ADHESIVE	N/A
RELEASE PAPER	Film liner
TEMPERATURE RANGE	-30°C to +80°C
DURABILITY (UNPRINTED)	Up to 1 year
FLAME RETARDANCY	B1
TOP COAT	N/A
TENSILE STRENGTH	800 / 1000 (N / 5cm)
TEAR RESISTANCE	400 / 400 (N)
SHELF LIFE	6 months, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2007 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.