

This perforated window film has a 60% printable surface with 1.5mm holes. It features a black acrylic adhesive and has been specifically designed for digital printing on large and wide-format inkjets. It is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2701

This perforated window film has been specifically designed for printing with all solvent and UV inks. IP 2701 can be used on flat surfaces and is intended for indoor and short-term outdoor applications. When printed, the film offers two different views: the front side with the graphic, the reverse side with a clear view through the perforations. Do not wet apply. To obtain good through vision and protection against moisture and abrasion, we recommend overlaminating. Laminate: IP 2830-100.

Specifications	
DESCRIPTION	Window marking film, perforated / 60% printable surface with 1.5mm holes
COLOUR	White
FACE FILM THICKNESS	140 $\mu$
WEIGHT	N/A
ADHESIVE	Acrylic black, permanent
ADHESIVE STRENGTH	12N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 135g / m <sup>2</sup>
TEMPERATURE RANGE	-40°C to +80°C
DURABILITY (UNPRINTED)	Up to 3 years
FLAME RETARDANCY	Adhered to steel, self-extinguishing
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2009 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.